

TOURING	FLHR Road King®	FLHRXS Road King® Special	FLHTK Ultra Limited	FLHX Street Glide®	FLHXS Street Glide® Special
Engine					
Engine	Milwaukee-Eight® 107	Milwaukee-Eight™ 114	Twin-Cooled™ Milwaukee-Eight™ 114	Milwaukee-Eight® 107	Milwaukee-Eight™ 114
Bore (*Cert) (X.XXX in) (XXX.X mm)	3.937 in. (100 mm)	4.016 in. (102 mm)	4.016 in. (102 mm)	3.937 in. (100 mm)	4.016 in. (102 mm)
Stroke (*Cert) (X.XXX in) (XXX.X mm)	4.374 in. (111.1 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)	4.375 in. (111 mm)	4.5 in. (114 mm)
Displacement (*Cert) (XXX.X cu in) (X,XXX cc)	107 cu in (1,746 cc)	114 cu in (1,868 cc)	114 cu in (1,868 cc)	107 cu in (1,746 cc)	114 cu in (1,868 cc)
Compression Ratio (*Cert)	10.0:1	10.5:1	10.5:1	10.0:1	10.5:1
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)
Exhaust	Chrome, 2-1-2 dual exhaust with tapered mufflers	Black, 2-1-2 dual exhaust with tapered mufflers	Chrome, 2-1-2 dual exhaust with tapered mufflers	Chrome, 2-1-2 dual exhaust with tapered mufflers	Black, 2-1-2 dual exhaust with tapered mufflers
Dimensions					
Length (*Cert) (XXX.X in) (X,XXX mm)	96.5 in. (2,450 mm)	95.3 in. (2,420 mm)	102.3 in. (2,600 mm)	96.5 in. (2,450 mm)	95.5 in. (2,425 mm)
Seat Height, Laden (XX.X in) (XXX mm)	26.3 in. (667 mm)	26.4 in. (671 mm)	27.5 in. (699 mm)	26.1 in. (664 mm)	26.1 in. (664 mm)
Ground Clearance (*Cert) (X.X in) (XXX mm)	5.3 in. (135 mm)	4.9 in. (125 mm)	5.3 in. (135 mm)	5.3 in. (135 mm)	4.9 in. (125 mm)
Rake (steering head) (deg) (XX.X)	26	26	26	26	26
Trail (X.X in) (XXX mm)	6.7 in. (170 mm)	6.9 in. (175 mm)	6.7 in. (170 mm)	6.7 in. (170 mm)	6.8 in. (173 mm)
Wheelbase (*Cert) (XX.X in) (XXX mm)	64 in. (1,625 mm)	64 in. (1,625 mm)	64 in. (1,625 mm)	64 in. (1,625 mm)	64 in. (1,625 mm)
Tires, Front Specification	BW 130/70B18 63H	130/60B19 61H	BW 130/70B18 63H	130/60B19 61H	130/60B19 61H
Tires, Rear Specification	BW 180/55B18 80H	180/55B18 80H	BW 180/55B18 80H	BW 180/55B18 80H	180/55B18 80H
Fuel Capacity (X.X gal) (XX.X mm)	6 gal. (22.7 l)	6 gal. (22.7 l)	6 gal. (22.7 l)	6 gal. (22.7 l)	6 gal. (22.7 l)
Oil Capacity (w/filter) (X.X qt) (X.X l)	5.2 qt. (4.9 l)	5.2 qt. (4.9 l)	5 qt. (4.7 l)	5.2 qt. (4.9 l)	5.2 qt. (4.9 l)
Weight, As Shipped (*Cert) (XXXX lb) (XXX kg)	794 lb. (360 kg)	774 lb. (351 kg)	880 lb. (399 kg)	796 lb. (361 kg)	792 lb. (359 kg)
Weight, In Running Order (*Cert) (XXXX lb) (XXX kg)	828 lb. (375 kg)	807 lb. (366 kg)	917 lb. (416 kg)	829 lb. (376 kg)	827 lb. (375 kg)
Luggage Capacity -Volume (X.X cu ft) (X.XXX m ³)	2.3 cu ft (0.064 m ³)	2.5 cu ft (0.07 m ³)	4.7 cu ft (0.132 m ³)	2.3 cu ft (0.064 m ³)	2.5 cu ft (0.071 m ³)
Performance					
Engine Torque Testing Method (*Cert)	J1349	J1349	J1349	J1349	J1349
Engine Torque (*Cert)	111 ft-lb (151 Nm)	111 ft-lb (151 Nm)	114 ft-lb (154 Nm)	111 ft-lb (151 Nm)	111 ft-lb (151 Nm)
Engine Torque (rpm) (*Cert)	3,250	3,250	3,250	3,250	3,250
Lean Angle, Right (deg.) (XX.X)	32	32	32	31	32
Lean Angle, Left (deg.) (XX.X)	32	31	32	29	31
Fuel Economy Testing Method	Estimated City/Hwy	Estimated City/Hwy	Estimated City/Hwy	Estimated City/Hwy	Estimated City/Hwy
Fuel Economy (XX mpg) (XX.X l/100 km)	45 mpg (5.2 l/100 km)	45 mpg (5.2 l/100 km)	43 mpg (5.5 l/100 km)	45 mpg (5.2 l/100 km)	45 mpg (5.2 l/100 km)
Drivetrain					
Primary Drive (*Cert)	Chain, 34/46 ratio	Chain, 34/46 ratio	Chain, 34/46 ratio	Chain, 34/46 ratio	Chain, 34/46 ratio
Gear Ratios (overall) 1st (*Cert) (X.XXX)	9.593	9.593	9.593	9.593	9.593
Gear Ratios (overall) 2nd (*Cert) (X.XXX)	6.65	6.65	6.65	6.65	6.65
Gear Ratios (overall) 3rd (*Cert) (X.XXX)	4.938	4.938	4.938	4.938	4.938
Gear Ratios (overall) 4th (*Cert) (X.XXX)	4	4	4	4	4
Gear Ratios (overall) 5th (*Cert) (X.XXX)	3.407	3.407	3.407	3.407	3.407
Gear Ratios (overall) 6th (*Cert) (X.XXX)	2.875	2.875	2.875	2.875	2.875
Chassis					
Wheels, Optional Style Type	N/A	N/A	Gloss Black Slicer II	N/A	N/A
Wheels, Front Type	Slicer II Cast Aluminum	Gloss Black Prodigy	Slicer II cast aluminum with clear coat	Enforcer II Cast Aluminum	Gloss Black Prodigy
Wheels, Rear Type	Slicer II Cast Aluminum	Gloss Black Prodigy	Slicer II cast aluminum with clear coat	Enforcer II Cast Aluminum	Gloss Black Prodigy
Brakes, Caliper Type	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear
Electric					
Lights (as per country regulation), Indicator Lamps	High beam, running lights, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, battery, security system, low fuel warning, cruise control, ABS, Gear/RPM display, miles to empty display	High beam, running lights, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, battery, security system, low fuel warning, cruise control, ABS, Gear/RPM display, miles to empty display	High beam, running lights, front fender running lights, directional lights, neutral, low oil pressure, engine diagnostics, accessory, speakers, turn signals, security system, gear indication, battery, low fuel warning, cruise control, ABS, fog/aux lamp indicator	High beam, running lights, directional lights, low oil pressure, engine diagnostics, neutral, cruise control, speakers, accessory, battery, gear indication, security system, 6-speed, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator	High beam, running lights, directional lights, low oil pressure, neutral, engine diagnostics, battery, cruise control, speakers, accessory, security system, gear indication, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator
Gauges	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.
Infotainment					
Infotainment system	N/A	N/A	Boom!™ Box GTS	Boom!™ Box 4.3	Boom!™ Box GTS
Type	N/A	N/A	Full Color TFT	Color	Full Color TFT
Watts Per Channel	N/A	N/A	25	25	25
Speakers	N/A	N/A	4	2	2
Speaker Size	N/A	N/A	5.25 inch standard	5.25 inch standard	6.5 inch BOOM standard
Headset Specifications (if equipped)	N/A	N/A	16-64 ohms	16-64 ohms	16-64 ohms
USB	N/A	N/A	USB/MTP/iPod/iPhone	USB/MTP/iPod/iPhone	USB/MTP/iPod/iPhone
Bluetooth	N/A	N/A	Phone/Media Supported	Phone/Media Supported	Phone/Media Supported

FLTRX Road Glide®	FLTRXS Road Glide® Special	FLTRK Road Glide® Limited	FLHT Electra Glide® Standard
Milwaukee-Eight® 107	Milwaukee-Eight™ 114	Twin-Cooled™ Milwaukee-Eight® 114	Milwaukee-Eight® 107
3.937 in. (100 mm)	4.016 in. (102 mm)	4.016 in. (102 mm)	3.937 in. (100 mm)
4.375 in. (111 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)	4.375 in. (111 mm)
107 cu in (1,746 cc)	114 cu in (1,868 cc)	114 cu in (1,868 cc)	107 cu in (1,746 cc)
10.0:1	10.5:1	10.5:1	10.0:1
Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)	Electronic Sequential Port Fuel Injection (ESPFI)
Chrome, 2-1-2 dual exhaust with tapered mufflers	Black, 2-1-2 dual exhaust with tapered mufflers	Chrome dual exhaust with 4 in. touring mufflers and touring muffler shields	Chrome, 2-1-2 dual exhaust with tapered mufflers
95.7 in. (2,430 mm)	95.7 in. (2,430 mm)	102.2 in. (2,595 mm)	94.5 in. (2,400 mm)
25.9 in. (658 mm)	25.9 in. (658 mm)	27.2 in. (690 mm)	26.1 in. (663 mm)
5.5 in. (140 mm)	5.1 in. (130 mm)	5.1 in. (130 mm)	4.9 in. (125 mm)
26	26	26	26
6.8 in. (173 mm)	6.8 in. (173 mm)	6.7 in. (170 mm)	6.7 in. (170 mm)
64 in. (1,625 mm)	64 in. (1,625 mm)	64 in. (1,625 mm)	64 in. (1,625 mm)
130/60B19 61H	130/60B19 61H	BW 130/70B18 63H	BW 130/80B17 65H
BW 180/55B18 80H	180/55B18 80H	BW 180/55B18 80H	BW 180/65B16 81H
6 gal. (22.7 l)	6 gal. (22.7 l)	6 gal. (22.7 l)	6 gal. (22.7 l)
5.2 qt. (4.9 l)	5.2 qt. (4.9 l)	5 qt. (4.7 l)	5.2 qt. (4.9 l)
820 lb. (372 kg)	818 lb. (371 kg)	897 lb. (407 kg)	781 lb. (354 kg)
855 lb. (388 kg)	853 lb. (387 kg)	932 lb. (423 kg)	820 lb. (372 kg)
2.3 cu ft (0.064 m ³)	2.7 cu ft (0.071 m ³)	4.7 cu ft (0.132 m ³)	2.3 cu ft (0.064 m ³)
J1349	J1349	J1349	J1349
111 ft-lb (151 Nm)	111 ft-lb (151 Nm)	122 ft-lb (166 Nm)	111 ft-lb (151 Nm)
3,250	3,250	3,000	3,250
31	32	31.9	31
29	31	31.8	29
Estimated City/Hwy	Estimated City/Hwy	Estimated City/Hwy	Estimated City/Hwy
45 mpg (5.2 l/100 km)	45 mpg (5.2 l/100 km)	43 mpg (5.5 l/100 km)	43 mpg (5.5 l/100 km)
Chain, 34/46 ratio	Chain, 34/46 ratio	Chain, 34/46 ratio	Chain, 34/46 ratio
9.593	9.593	9.593	9.593
6.65	6.65	6.65	6.65
4.938	4.938	4.938	4.938
4	4	4	4
3.407	3.407	3.407	3.407
2.875	2.875	2.875	2.875
N/A	N/A	Gloss Black Slicer II	N/A
Enforcer II Cast Aluminum	Gloss Black Prodigy	Slicer II cast aluminum with clear coat	Impeller Cast Aluminum
Enforcer II Cast Aluminum	Gloss Black Prodigy	Slicer II cast aluminum with clear coat	Impeller Cast Aluminum
32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear	32 mm, 4-piston fixed front and rear
High beam, running lights, directional lights, low oil pressure, neutral, engine diagnostics, battery, cruise control, speakers, accessory, security system, gear indication, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator	High beam, running lights, directional lights, low oil pressure, neutral, engine diagnostics, battery, cruise control, speakers, accessory, security system, gear indication, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator	High beam, neutral, running lights, turn signals, low oil pressure, engine diagnostics, cruise control, speakers, accessory, security system, 6-speed, low fuel warning, ABS.	High beam, running lights, directional lights, low oil pressure, engine diagnostics, neutral, cruise control, accessory, battery, gear indication, security system, 6-speed, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator
Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.
Boom!™ Box 4.3	Boom!™ Box GTS	Boom!™ Box GTS	N/A
Color	Full Color TFT	Full Color TFT	N/A
25	25	25	N/A
2	2	4	N/A
5.25 inch standard	6.5 inch BOOM standard	5.25 inch standard	N/A
16-64 ohms	16-64 ohms	16-64 ohms	N/A
USB/MTP/iPod/iPhone	USB/MTP/iPod/iPhone	Phone/Media Supported	N/A
Phone/Media Supported	Phone/Media Supported	Phone/Media Supported	N/A

in der Schweiz nicht erhältlich